


Health	1
Flammability	2
Reactivity	1
PPE	G

MATERIAL SAFETY DATA SHEET



769 LUBRICANT - AEROSOL

HMIS SYMBOL

NFPA SYMBOL

SECTION 1 - PRODUCT NAME AND COMPANY IDENTIFICATION

Product Name: **769 Lubricant - Aerosol**
 Chemical Family: Mixture
 Use: Penetrating lubricant, cleaner & corrosion inhibitor.
 Manufacturer/Supplier: Jet-Lube of Canada Ltd.
 3820 - 97 Street
 Edmonton, Alberta
 Canada T6E 5S8
 Phone: (780) 463-7441 Fax: (780) 463-7454
 CCOHS: 1-800-263-8466

Emergency:

CANUTEC Phone: (613) 996-6666 Cellular: *666 TTY/TDD: 1-888-675-6863

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	Propellant	Hydrotreated Kerosene
CAS No	124-38-9	64742-47-8
Wt. %	4 Max.	65 Max.
OSHA PEL	5,000 mg/L	Not Established
ACGIH TLV	5,000 mg/L	200 mg/m ³
LC50	Not Determined	Not Determined
LD50	Not Determined	Not Determined
Other, AIHA	N/A	N/A

SECTION 3 - HAZARDS IDENTIFICATION

Route of Entry: Eyes, ingestion, inhalation, skin
 Eyes: May cause transient irritation and pain to eyes.
 Ingestion: May cause diarrhea, if ingested.
 Inhalation: May cause breathing difficulty.
 Skin: May cause transient irritation to skin. Possible rash for persons with hypersensitivity.

SECTION 4 - FIRST AID MEASURES

Eyes: Flush with water until all residual material is gone. If irritation persists, seek medical help.
 Ingestion: Do not induce vomiting. Wash out mouth. Contact a physician immediately.
 Inhalation: Remove to fresh air. If respiratory difficulty persists, seek medical help.
 Skin: Remove by wiping or with a waterless hand cleaner, followed by washing with soap and water.

SECTION 5 - FIRE FIGHTING MEASURES

Flammability: Flammable
 Extinguishing Media: Use dry chemicals, foam, halon, or CO₂.
 Flash Point (COC): 79°C (174°F)
 Explosive Properties: LEL - 1.50% UEL - <10.5%
 Autoignition Temperature: 229°C (444°F)
 Hazardous Combustion Products: Oxides of carbon, smoke and irritating vapors as products of incomplete combustion.
 Protective Equipment: Self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spillage: Scoop up excess, then wipe down the affected area and pick up residue with diatomaceous earth to avoid a walking hazard.
 Environmental Precautions: Avoid disposal into drains.

SECTION 7 - HANDLING AND STORAGE

Handling Procedures: No special handling precautions necessary. Do not pressurize, cut, heat or weld empty containers.
 Storage Requirements: Store in a cool, well ventilated place.
 Engineering Controls: If user's operation generates vapors or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make up air should always be supplied to balance air removed by exhaust ventilation. Ensure eyewash station and safety shower are close to work station.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protection Equipment (PPE's)
 Respiratory Protection: Breathing apparatus in confined space areas.
 Hand Protection: Protective gloves for hypersensitive persons.
 Eye Protection: Protective glasses if applied to moving parts.
 Body Protection: Protective overalls.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Aerosol Form
 Odour: Petroleum
 Odour Threshold: Not Determined
 Vapor Pressure: <0.01 kPa
 Boiling Point: >149°C (300°F)
 pH: Neutral
 Density, Typical: 0.83 kg/L
 Evaporation Rate (Butyl Acetate = 1.0): <0.01
 Specific Gravity, Typical: 0.83
 Vapor Density: >5
 % Volatile: Not Determined
 Melting Point: -40°C (-40°F)
 Water Solubility: Nil

SECTION 10 - STABILITY AND REACTIVITY

Stability: Chemically stable under normal conditions.
 Photoreactive Agents: None
 Conditions to Avoid: Powerful sources of ignition, extreme temperatures.
 Materials to Avoid: Reactive and oxidizing agents.
 Hazardous Decomposition Products: May release CO_x, smoke and irritating vapors when heated to decomposition.

SECTION 11 - TOXICOLOGICAL INFORMATION

Exposure Limit of Material: See Section 2
 LC50 of Ingredients, Species and Routes: See Section 2
 LD50 of Ingredients, Species and Routes: See Section 2
 Teratogenicity, Embryotoxicity and/or Fetotoxicity: Not Available
 Mutagenicity: Not Available
 Effects of Long-Term (Chronic) Exposure: Long term dermal application may produce possible skin irritation. Elevated temperatures or mechanical action may form vapors or fumes. Inhalation of oil mists or vapors from hot oil may cause irritation of the upper respiratory tract.

Carcinogen NTP: No IARC: No OSHA: No

SECTION 12 - ECOLOGICAL INFORMATION

Possible Effects: May generate oil fractions that could act as a marine pollutant, but is highly unlikely.
 Behavior: Relatively well behaved. Bioaccumulation potential nil.
 Environmental Fate: Product will float and spread across water making it a nuisance contaminant.

SECTION 13 - DISPOSAL CONSIDERATIONS

Consult federal, provincial and local regulations for disposal of aerosol products.

SECTION 14 - TRANSPORT INFORMATION

General Product Classification:

Product is a mixture and contains controlled components.
 Classification: Class 2.1, Flammable Gases
 Shipping Name: AEROSOL, Flammable
 UN No.: UN1950

TDG Shipping Information:

Packing Group: None
 Labelling Requirements: Limited Quantities label for containment less than LQI of 6 L net contents per containment. Class 2.1 label if >6 L net contents per containment or large containment.
 Placard Requirements: Limited Quantities - None Required
 Large Containment - Class 2.1

IATA & ICAO Shipping Information:

Packing Instructions: 203 (Refer to ICAO Technical Instructions)
 Limited Quantity Exemption: 75 kg for Passenger Aircraft (some provision limiting amount to only 30 kg)
 150 kg for Cargo Aircraft

SECTION 15 - REGULATORY INFORMATION

WHMIS: Class A, B-5
 DSL: All components listed.
 CPR Compliance: This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations. The MSDS contains all of the information required by these regulations.

SECTION 16 - OTHER INFORMATION

CPR - Controlled Product Regulations LQI - Limited Quantity Index
 DSL - Domestic Substance List

As of issue date, the information contained herein is accurate and reliable to the best of Jet-Lube of Canada Ltd.'s knowledge. Jet-Lube of Canada Ltd. does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the users' responsibility to satisfy themselves that the information offered for their consideration is suitable for their particular use.

Prepared By: **Jet-Lube of Canada Ltd. - Laboratory**
 Last Date of Revision: **November 26, 2007**