


Health	1
Flammability	1
Reactivity	0
PPI	B

# MATERIAL SAFETY DATA SHEET

## EZY-TURN® #2



### HMIS SYMBOL

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: **EZY-TURN® #2**  
 Chemical Family: Mixture  
 Use: Lubricating grease & sealant for valves.  
 Manufacturer/Supplier: **Jet-Lube of Canada Ltd.**  
 3820 - 97 Street  
 Edmonton, Alberta  
 Canada T6E 5S8  
 Phone: (780) 463-7441 Fax: (780) 463-7454  
 CCOHS: 1-800-668-4284

**Emergency:**  
 CANUTEC PH: (613) 996-6666 Cell: \*666 TTY/TDD: 1-888-675-6863

### SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component	Fumed Silica	Propylene Glycol
CAS NO:	112945-52-5	57-55-6
Wt %:	3 - 7	0.1 - 1
OSHA PEL	Not Established	Not Determined
ACGIH TLV	10.0 mg/m <sup>3</sup> (inhalable particles)	Not Determined
LD50	3160 mg/kg (rat, oral)	15.7-19.2 g/kg (oral, rabbit)
LC50	Not Determined	20.8g/kg (dermal, rabbit)
Other:	N/A	N/A

### SECTION 3 - HAZARDS IDENTIFICATION

Route of Entry: Eyes, Inhalation, Ingestion, Skin  
 Eyes: May cause irritation to eyes.  
 Inhalation: Not a typical route of occupational exposure. Viscous nature may block breathing passages if inhaled.  
 Ingestion: Not a typical route of occupational exposure. Very slightly hazardous in the case of ingestion.  
 Skin: May cause irritation after prolonged skin exposure, especially for persons with hyper sensitivity.

### SECTION 4 - FIRST AID MEASURES

Eyes: Flush with water until all residual material is gone. If irritation persists, seek medical help.  
 Ingestion: Do not induce vomiting. Wash out mouth. Contact a physician immediately.  
 Skin: Remove by wiping or with a waterless hand cleaner, followed by washing with soap and water.  
 Inhalation: Clear air passage. If breathing difficulty continues seek medical help.

### SECTION 5 - FIRE FIGHTING MEASURES

Flammability: Nil at ambient temp  
 Extinguishing Media: Use dry chemicals, foam, halon, CO2  
 Flash Point (COC): >204°C (400°F)  
 Explosive Properties: LEL -UN UEL - UN  
 Autoignition Temp: >260°C (500°F)  
 Hazardous Combustion Products: Oxides of carbon, sulfur and nitrogen vapors as products of incomplete combustion.  
 Protective Equipment: Self-contained breathing apparatus.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spillage: Scoop up excess, then wipes down the affected area and pick up residue with diatomaceous earth to avoid a walking hazard.  
 Environmental Precautions: Avoid dispersal into drains.

### SECTION 7 - HANDLING AND STORAGE

Handling Procedures: No special handling precautions necessary. Do not pressurize, cut, heat or weld empty containers.  
 Storage Requirements: Store in a cool, well ventilated place.  
 Engineering Controls: If user's operation generates vapors or mists, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make up air should always be supplied to balance air removed by exhaust ventilation. Ensure eyewash station and safety shower are close to work station.

### SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Equipment (PPE's):  
 Respiratory Protection: None required.  
 Hand Protection: Protective gloves for hypersensitive persons.  
 Eye Protection: Protective glasses if applied to moving parts.  
 Body Protection: Protective Overalls.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Paste  
 Odor: Petroleum  
 Odor Threshold: Not Determined  
 Specific Gravity: 1.05 Typical  
 Vapor Pressure: <0.01 kPa  
 Vapor Density: >5  
 Boiling Point: >316°C (600°F)  
 Melting Point: Not Determined  
 pH: Neutral  
 Density: 1.05 g/cm<sup>3</sup>  
 Evaporation Rate (Butyl Acetate = 1.0): <0.01

### SECTION 10 - STABILITY AND REACTIVITY

Stability: Chemically stable under normal conditions. No photoreactive agents.  
 Conditions to Avoid: Powerful sources of ignition and extreme temperatures.  
 Materials to Avoid: Strong acids and oxidizing agents  
 Hazardous Decomposition Products: Burning generates smoke, airborne soot, hydrocarbons and oxides of carbon, sulfur and nitrogen. Residue mainly comprised of mineral oxides and soot.

### SECTION 11 - TOXICOLOGICAL INFORMATION

Exposure Limit of Material: See Section 2.  
 LC50 of Ingredients, Species and Routes: See Section 2.  
 LD50 of Ingredients, Species and Routes: See Section 2.  
 Teratogenicity, Embryotoxicity and/or Fetotoxicity: Not Available  
 Mutagenicity: Not Available  
 Effects of Long-Term (Chronic) Exposure: Long term dermal application may produce possible skin irritation. Elevated temperatures or mechanical action may form vapors or fumes. Inhalation of oil mists or vapors may cause irritation of the upper respiratory tract.  
 Carcinogen: NTP: No IARC: No OSHA: No

### SECTION 12 - ECOLOGICAL INFORMATION

Possible Effects: No known possible effects that could act or be classified as a marine pollutant.  
 Behavior: Well behaved.  
 Environmental Fate: Possibility of hazardous short term degradation products are not likely. However, long term effects of degradation products may arise.

### SECTION 13 - DISPOSAL CONSIDERATIONS

Consult federal, provincial and local regulations for disposal of petroleum products. Do not incinerate.

### SECTION 14 - TRANSPORT INFORMATION

TDG (Canada): The mixture is not specifically listed in the Canadian Transportation of Dangerous Goods regulations. The mixture is not regulated.  
 Land & Rail: Not Regulated  
 Marine: Not Regulated  
 Shipping Name: N/A  
 UN No.: N/A  
 Packing Group: N/A  
 Classification: N/A  
 Labeling Requirements: N/A  
 Placard Requirements: N/A

### SECTION 15 - REGULATORY INFORMATION

WHMIS: Not Controlled  
 DSL: All components listed  
 CPR Compliance: This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by those regulations.

### SECTION 16 - OTHER INFORMATION

CPR - Controlled Product Regulations  
 DSL - Domestic Substance List

As of issue date, the information contained herein is accurate and reliable to the best of Jet-Lube of Canada Ltd.'s knowledge. Jet-Lube of Canada Ltd. does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the users' responsibility to satisfy themselves that the information offered for their consideration is suitable for their particular use.

Prepared by: **Jet-Lube of Canada Ltd. - Laboratory**  
 Last Date of Revision: **July 14, 2009**