

# API-MODIFIED

## High Pressure Thread Compound



### TECHNICAL DATA SHEET

3820 - 97 Street, NW, Edmonton, Alberta Canada T6E 5S8 • Phone (780) 463-7441 Toll Free 1-888-771-7775 Fax (780) 463-7454 Toll Free 1-888-449-4449  
email: sales@jetlubecanada.com Web site: www.jetlubecanada.com

#### DESCRIPTION

**JET-LUBE API-MODIFIED** is a high pressure thread sealing compound which is formulated according to the guidelines of API BUL 5A3. It also contains rust and oxidation inhibitors blended into Jet-Lube's unique grease, compounded from custom-refined low-sulphur oil to ensure brushability over a wide temperature range, tenacious adherence to thread surfaces, resistance to water washout, and prevention of rust and corrosion. **API-MODIFIED** is conductive, which reduces the possibility of electrolytic corrosion by preventing the formation of galvanic cells in the presence of salt water and other corrosive fluids.

**API-MODIFIED** will seal and withstand pressures to 69,000 kPa (10,000 psi) and will not harden or dry. Its lubricating characteristics reduce friction in the makeup of casing and tubing, preventing galling and wear. Maximum thread engagement is ensured, providing optimum leak resistance.

#### APPLICATIONS

**JET-LUBE API-MODIFIED** is specifically formulated for use on casing, tubing, line pipe, flow lines, subsurface production tools, tank batteries, etc. It will lubricate, seal and protect threaded connections of oilfield tubular goods on makeup, in service and in storage.

NOT RECOMMENDED FOR  
ROTARY SHOULDERED CONNECTIONS

#### OPERATING RANGE

Temperatures from -18°C to 205°C (0°F to 400°F)  
Pressures from 69,000 kPa (10,000 psi)



#### CHARACTERISTICS

- Manufactured to API BUL 5A3 requirements
- Additives for rust and corrosion protection
- Excellent lubrication qualities to prevent galling and wear
- Sticks to wet or oily threads
- Brushable over a wide temperature range
- Leak prevention to 60,000 kPa (10,000 psi)

#### PRODUCT SPECIFICATIONS

Grease Base	36.0% ± 1.0%
Powdered Graphite	18.0% ± 1.0%
Lead Powder	30.5% ± 0.6%
Zinc Dust	12.2% ± 0.6%
Copper Flake	3.3% ± 0.3%
Thickener	Aluminum Stearate
Fluid Type	Petroleum
Color/Appearance	Black/Brown
Dropping Point (ASTM D-566)	90°C (195°F)
Specific Gravity, Typical	1.70
Density (kg/liter), Typical	1.70
Flash Point (ASTM D-92)	221°C (430°F)
Water Spray-Off (ASTM-4049)	<10%
NLGI Grade	2
Copper Strip Corrosion (ASTM D-4048)	1A

#### PACKAGING

Inventory Code	Container Size	Container
22109	9 Kg	Pail
22114	15 Kg	Pail
22125	25 Kg	Pail

Certification API RP 5A3

#### LIMITED WARRANTY

Jet-Lube of Canada makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube of Canada Ltd. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube of Canada Ltd.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube of Canada Ltd. shall not be liable for incidental or consequential damages.