

CB-2™

Multi-Purpose Grease



TECHNICAL DATA SHEET

3820 - 97 Street, NW, Edmonton, Alberta Canada T6E 5S8 • Phone (780) 463-7441 Toll Free 1-888-771-7775 Fax (780) 463-7454 Toll Free 1-888-449-4449
email: sales@jetlubecanada.com Web site: www.jetlubecanada.com

DESCRIPTION

CB-2 is an all-purpose, high quality, Lithium 12-Hydroxystearate soap grease. Its buttery consistency makes it highly adhesive to metal and it has exceptional mechanical stability. **CB-2** is standard in an NLGI 2 Grade grease that will accommodate nearly all requirements for a "multipurpose" grease type lubricant. It is a truly versatile product.

CB-2 has exceptional resistance to the effects of heat, water, oxidation and heavy loadings. It is water resistant and contains corrosion and oxidation inhibitors. **CB-2** offers protection wherever dirt, dust, high humidity, rain and adverse temperatures are critical problems. It is an all-weather product that lubricates efficiently at temperatures as low as -18°C (0°F). For lower temperatures, Jet-Lube's ARCTIC™ is recommended.

CB-2 can be used as a chassis grease for automobiles, trucks, forklifts, or all mobile machinery. Use also on springs, universal joints and water pumps.

CHARACTERISTICS

- Protects against rust and corrosion
- Pumpable
- Highly adhesive to metal
- Resistant to heat, water, oxidation & heavy loading
- High film strength

APPLICATIONS

CB-2 is specifically formulated for use on fast running bearings, anti-friction bearings, journals and all general greasing where a single, multi-purpose product is desired for economy, simplification of inventory and greasing equipment. **CB-2** may be used on fans, blowers, pumps, conveyor bearings, drive trains, ball bearings, journal bearings, roller bearings, screw jackets, universal joints and all other lubrication points having sliding or rolling friction that requires a multi-purpose grease. This product may be used on oil drilling rigs, on construction and road building equipment, in mining and ship building activities, or wherever an exceptionally high-quality lubricant is required.

NOTE:

For automotive, truck or trailer wheel bearing use, Jet-Lube ALCO-EP ECF is recommended.

LIMITED WARRANTY

Jet-Lube of Canada makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube of Canada Ltd. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube of Canada Ltd.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube of Canada Ltd. shall not be liable for incidental or consequential damages.

PRODUCT SPECIFICATIONS

Thickener	Lithium 12-Hydroxy Petroleum Oil
Fluid Type	Amber to Brown
Color/Appearance	200°C (390°F)
Dropping Point (ASTM D-566)	0.90
Specific Gravity, Typical	0.90
Density (kg/liter), Typical	Organic EP, AW, R&O
Additive Type	>220°C (430°F)
Flash Point (ASTM D-92)	>260°C (500°F)
Autoignition Point (Calculated)	2
NLGI Grade	265 - 295
Penetration @ 25°C (77°F) (ASTM D-217)	1A
Copper Strip Corrosion (ASTM D-4048)	200
Shell 4 Ball (ASTM D-2596)	25
Weld Point, kgf	0.7
Load Wear Index	Oxidation Resistance (ASTM D-942)
Wear Scar Diameter (ASTM D-2266)	psi Drop, 100 hours
Oxidation Resistance (ASTM D-942)	<5
psi Drop, 100 hours	100 - 160
Base Oil Viscosity (ASTM D-445), cSt @ 40°C	

OPERATING RANGE

-18°C to 150°C (0°F to 300°F)

PACKAGING

Inventory Code	Container Size	Container
31050	14 oz.	Cartridge
31003	1 Lb.	Can
31006	5 Lb.	Can
31016	35 Lb.	Pail
31024	120 Lb.	Keg
31029	400 Lb.	Drum

