

CC-LUBE™

Clear, Clean, Semi-Synthetic Multi-Purpose Lubricant



TECHNICAL DATA SHEET

3820 - 97 Street, NW, Edmonton, Alberta Canada T6E 5S8 • Phone (780) 463-7441 Toll Free 1-888-771-7775 Fax (780) 463-7454 Toll Free 1-888-449-4449
email: sales@jetlubcanada.com Web site: www.jetlubcanada.com

DESCRIPTION

CC-LUBE™ is a state-of-the-art, semi-synthetic, multi-purpose lubricant that combines an aluminum complex thickener for extreme water resistance with the latest synthetic ingredients and PTFE to create a totally transparent, long-lasting, high lubricity lubricant with unequalled quality and performance.

CC-LUBE is clear, clean, colorless, nonstaining, nondrying, biodegradable and unsurpassed in reducing friction, extending machine and equipment life and preventing the formation of rust and corrosion over a broad temperature range. **CC-LUBE** is CFIA approved and NSF (H-1) authorized for use in Federally Inspected Meat and Poultry Plants.

CHARACTERISTICS

- Nontoxic, Nonstaining
- Clear, Clean Lubricant
- Nondrying Formula
- Colorless/Odorless
- Contains PTFE
- CFIA & NSF (H-1) authorized
- Prevents rust, corrosion
- Biodegradable
- Extremely water resistant
- Reduces friction

APPLICATIONS

CC-Lube is designed to eliminate how water washout and has anti-bacterial additives to eliminate bacterial culturing. It may be safely used on a variety of surfaces including metal, plastic, rubber (viton, neoprene, buna & HSN), vinyl, stainless steel and nylon, in a multitude of automotive, electrical, food processing, industrial, marine and residential applications, including:

Bearings	Bushings	Conveyors
Hinges	Industrial Equipment	Locks
Food Machinery	Pulleys	Pumps
Slides	Valves	Winches

OPERATING RANGE

-18° C to 204° C (0°F to 400°F)



PRODUCT SPECIFICATIONS

Thickener	Aluminum Complex
Fluid Type	White Oils & Synthetics
Color/Appearance	Clear
Dropping Point (ASTM D-566)	260°C (500°F)
Specific Gravity, Typical	0.88
Density (kg/liter), Typical	0.88
Additive Type	Organic, R&O, PTFE
Flash Point (ASTM D-92)	>221°C (430°F)
Autoignition Point (Calculated)	>260°C (500°F)
NLGI Grade	1 - 1½
Penetration @ 25°C (77°F) (ASTM D-217)	285 - 315
Copper Strip Corrosion (ASTM D-4048)	1A
Shell 4 Ball (ASTM D-2596)	
Weld Point, kgf	126
Load Wear Index	25
Wear Scar Diameter (ASTM D-2266)	0.7
Oxidation Resistance (ASTM D-942)	
psi Drop, 100 hours	<5
Base Oil Viscosity (ASTM D-445), cSt @ 40°C	90 - 110

CERTIFICATIONS

Military Specifications - SAE-AMS-G4343 (S/S MIL-G-4343C)

NATO G392

CFIA & NSF Registered H1 - Reg. #048221 - for use in federally inspected meat and poultry plants



PACKAGING

Inventory Code	Container Size	Container
70550	14 oz.	Cartridge
70523	1-Gal.	Pail
70516	35 Lb.	Pail
70524	120 Lb.	Keg
70529	400 Lb.	Drum

LIMITED WARRANTY

Jet-Lube of Canada makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube of Canada Ltd. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube of Canada Ltd.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube of Canada Ltd. shall not be liable for incidental or consequential damages.