

EZY-TURN™ #22

Gate Valve Sealant & Body Filler Lubricant



TECHNICAL DATA SHEET

3820 - 97 Street, NW, Edmonton, Alberta Canada T6E 5S8 • Phone (780) 463-7441 Toll Free 1-888-771-7775 Fax (780) 463-7454 Toll Free 1-888-449-4449
email: sales@jetlubecanada.com Web site: www.jetlubecanada.com

DESCRIPTION

EZY-TURN™ #22 Gate Valve Sealant & Body Filler Lubricant is a premium sealant formulated from a unique blend of synthetic and vegetable based oils for use in WKM type valves. **EZY-TURN #22** contains no solid fillers that may inhibit valve lubrication. Although designed for WKM type valves, **EZY-TURN #22** can be effectively used on virtually any lubricated gate valve.

EZY-TURN #22 provides optimum sealability, lubricity and torque reduction while being hydrocarbon and water resistant. Easily injectable into the valve body using a high pressure lubricator. Ideal for use with gaseous services.

Recommended Cleanup: Although conventional solvents like methanol, ethanol, IPA, chlorinated solvents, aromatic solvents, acetone and other ketones can be utilized, Jet-Lube recommends its EZY-OPEN™ or other safe oxygenated solvents. EZY-OPEN is a nontoxic, nonflammable, biodegradable lubricant and cleanser specifically designed for valve cleaning applications. It contains no components listed as federal hazardous wastes.

APPLICATIONS

Oilfield: **EZY-TURN #22** has been formulated for use in production oilfield situations (Christmas trees, line valves) where a variety of service conditions may be encountered. This is a premium product and should be used where solid fillers mandated in the 'peanut butter' type sealants are not wanted.

EZY-TURN #22 is especially effective in gaseous hydrocarbon services. Recommended for services consisting of blends such as condensate crude or gas mixed with salt water, dilute alkalies or acids, or other foreign materials.

Industrial and Marine: **EZY-TURN #22** is also recommended for gate valve applications requiring resistance to hydrocarbon or hydrocarbon/water mixtures. Absence of solid fillers assures that the service will not be contaminated with unwanted solids.

SERVICE RECOMMENDATIONS

Petroleum Gases	Petroleum Liquids	Natural Gas
Crude Distillates	Dilute Alkalies	Aqueous Solutions
Butane	Propane	LPG
Crude Oil	Dilute Acids	Salt Solutions

Note: Not for use with oxygen or strong oxidizers.

OPERATING RANGE
-46°C to 149°C (-50°F to 300°F)

CHARACTERISTICS

- Synthetic & Vegetable Base
- No Solid Fillers
- Injectable
- Reduces Torque
- Nonhazardous
- Water Resistant
- Color: Amber
- Nontoxic
- Multi-Purpose
- Seals, Lubricates
- Biodegradable
- Hydrocarbon Resistant

PRODUCT SPECIFICATIONS

BULK

Appearance	Amber to Golden Sticky Paste or Semi-Plastic
Cone Penetration (ASTM D-217), MMx 10 ⁻¹	255 - 285
Density (lbs/gallon), Typical	10.23
Specific Gravity, Typical	1.02
Dropping Point (ASTM D-2265)	None
Oil Separation, Wt. % (FTMS 791.B M 321.2)	5.0 Max.
Thickener	Inorganic
Flash Point (ASTM D-92)	>282°C (540°F)

STICK

Appearance	Amber to Golden Sticky Paste or Semi-Plastic
Cone Penetration (ASTM D-217), MMx 10 ⁻¹	80 -130
Density (lbs/gallon), Typical	10.49
Specific Gravity, Typical	1.05
Dropping Point (ASTM D-2265)	None
Oil Separation, Wt. % (FTMS 791.B M 321.2)	1.0 Max.
Thickener	Inorganic
Flash Point (ASTM D-92)	>282°C (540°F)

PACKAGING

Inventory Code	Size	Description
96522	10 Lb.	Can
96516	40 Lb.	Pail
96524	120 Lb.	Keg
96529	400 Lb.	Drum



LIMITED WARRANTY

Jet-Lube of Canada makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube of Canada Ltd. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube of Canada Ltd.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube of Canada Ltd. shall not be liable for incidental or consequential damages.