

# **EASY-CLEAN<sup>®</sup> LIQUID**

## **ALKALINE CLEANER & DEGREASER CONCENTRATE**

### **DESCRIPTION**

**EASY-CLEAN LIQUID** is an alkaline based cleaner degreaser that uniquely combines cleaning agents with newly developed emulsifying technology to provide a product that can effectively remove carbon, grease, oil and other organic deposits while being both safe and ozone friendly. **EASY-CLEAN LIQUID** is tomorrow's answer to today's cleaning problems-totally effective yet safe for our environment and atmosphere. Use by pouring a five gallon pail into a drum then dilute with water filling the drum.

|               |                |               |
|---------------|----------------|---------------|
| Biodegradable | Noncombustible | Nonflammable  |
| Nonfuming     | Nontoxic       | Water Soluble |

**EASY-CLEAN LIQUID** contains no 1:1:1 Trichloroethane, Fluorocarbons or SARA Title III, Section 313, Part 372 listed ingredients and contains no acids, chlorides, phosphates of TTO's (Total Toxic Organic Compounds).

**EASY-CLEAN LIQUID** is the most effective cleaner/degreaser for heavy duty industrial services available and can be used for heavy duty parts degreasing, pressure washing, steam cleaning, ultrasound cleaning or simply by brushing or spraying and then rinsing with water or wiping clean. In its concentrated form, **EASY-CLEAN LIQUID** could be corrosive to aluminum and its alloys in its concentrated form.

### **APPLICATIONS**

|              |                    |                   |
|--------------|--------------------|-------------------|
| Construction | Oilfield Equipment | Metal Fabrication |
| Industrial   | Residential        | Marine            |
| Utilities    |                    |                   |

### **DILUTION RATIOS**

**EASY-CLEAN LIQUID** may be diluted with ordinary tap water or salt water (with reduced affect). Dilution ratios will vary greatly depending on the amount of buildup, temperature and speed required to complete the job. Suggested dilution ratios of water to **EASY-CLEAN LIQUID**:

| <u>DILUTE</u>                 | <u>EQUIPMENT</u>                        |
|-------------------------------|---|
| <b>E-C Liquid</b>             |   |
| to water                      |   |
| 1:10                          | Drilling and Construction Equipment     |
| 1:30                          | Upholstery, Interiors, Carpet           |
| 1:40                          | Fuel Oil Truck Bodies, General Cleaning |
| <b>High Pressure Sprayers</b> |   |
| 1:50                          | 150-300 psi Cold Water                  |
| 1:100                         | 150-300 psi Hot Water                   |
| 1:100                         | 500-800 psi Cold Water                  |
| 1:200                         | 500-800 psi Hot Water                   |

**RINSE AND WIPE DRY - TEST FOR COLOR FASTNESS**

### **PRODUCT CHARACTERISTICS**

|                               |                |
|-------------------------------|----------------|
| Specific Gravity              | 1.07           |
| pH                            | 14             |
| Viscosity (Cps)               | 4.5            |
| Flash Point (PMCC Closed Cup) | None to 212°F  |
| (ASTM D93)                    |                |
| Auto Ignition Point           | None to 500°F  |
| Vapor Pressure @ 20°C)        | Composite <.04 |
| Evaporation Rate              | <1             |
| (Butyl Acetate = 1)           |                |
| Vapor Density (Air = 1)       | >1             |
| Boiling Point                 | 212°F (100°C)  |
| Freezing Point                | 28°F           |

### **PACKAGING**

| <b>Code No.</b> | <b>Container Size</b> | <b>Container</b> |
|-----------------|-----------------------|------------------|
| 30033           | 1 gal.                | Jug              |
| 30035           | 5 gal.                | Jug              |
| 30029           | 50 gal.               | Drum             |

### **LIMITED WARRANTY**

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

## **CORPORATE LOCATIONS**

**Houston, Texas—World Headquarters**

**Maidenhead, England**

**Edmonton, Canada**

**JET-LUBE, INC.**  
**4849 HOMESTEAD RD.,**  
**P.O. BOX 21258 (77226-1258)**  
**HOUSTON, TX 77028**

**WATS: 800-538-5823**  
**PHONE: 713-674-7617**  
**FAX: 713-678-4604**  
**E-MAIL: sales@jetlube.com**  
**www.jetlube.com**

**OILFIELD**

**OILFIELD**

**OILFIELD**

**OILFIELD**

**OILFIELD**