

EASY-CLEAN[®] LIQUID

Alkaline Cleaner & Degreaser Concentrate



TECHNICAL DATA SHEET

3820 - 97 Street, NW, Edmonton, Alberta Canada T6E 5S8 • Phone (780) 463-7441 Toll Free 1-888-771-7775 Fax (780) 463-7454 Toll Free 1-888-449-4449
email: sales@jetlubecanada.com Web site: www.jetlubecanada.com

DESCRIPTION

EASY-CLEAN LIQUID is an alkaline based cleaner degreaser that uniquely combines cleaning agents with newly developed emulsifying technology to provide a product that can effectively remove carbon, grease, oil and other organic deposits while being both safe and ozone friendly. **EASY-CLEAN LIQUID** is tomorrow's answer to today's cleaning problems-totally effective yet safe for our environment and atmosphere. Use by pouring a five gallon pail into a drum then dilute with water filling the drum.

Biodegradable	Noncombustible	Nonflammable
Nonfuming	Nontoxic	Water Soluble

EASY-CLEAN LIQUID contains no 1:1:1 Trichloroethane, Fluorocarbons or SARA Title III, Section 313, Part 372 listed ingredients and contains no acids, chlorides, phosphates or TTO's (Total Toxic Organic Compounds).

EASY-CLEAN LIQUID is the most effective cleaner/degreaser for heavy duty industrial services available and can be used for heavy duty parts degreasing, pressure washing, steam cleaning, ultrasound cleaning or simply by brushing or spraying and then rinsing with water or wiping clean. In its concentrated form, **EASYCLEAN LIQUID** could be corrosive to aluminum and its alloys in its concentrated form.

APPLICATIONS

Construction Oilfield Equipment Metal Fabrication Industrial Residential Marine Utilities

DILUTION RATIOS

EASY-CLEAN LIQUID may be diluted with ordinary tap water or salt water (with reduced affect). Dilution ratios will vary greatly depending on the amount of buildup, temperature and speed required to complete the job. Suggested dilution ratios of water to EASY-CLEAN LIQUID:

DILUTE	EQUIPMENT
E-C Liquid to water	
1:10	Drilling and Construction Equipment
1:30	Upholstery, Interiors, Carpet
1:40	Fuel Oil Truck Bodies, General Cleaning
High Pressure Sprayers	
1:50	150-300 psi Cold Water
1:100	150-300 psi Hot Water
1:100	500-800 psi Cold Water
1:200	500-800 psi Hot Water

RINSE AND WIPE DRY - TEST FOR COLOR FASTNESS

PRODUCT CHARACTERISTICS

Specific Gravity	1.07
pH	14
Viscosity (Cps)	4.5
Flash Point (PMCC Closed Cup) (ASTM D93)	None to 212°F
Auto Ignition Point	None to 500°F
Vapor Pressure @ 20°C	Composite <.04
Evaporation Rate (Butyl Acetate = 1)	<1
Vapor Density (Air = 1)	>1
Boiling Point	212°F (100°C)
Freezing Point	28°F

PACKAGING

Inventory Code	Container Size	Container
30035	5 US Gal	Pail



LIMITED WARRANTY

Jet-Lube of Canada makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube of Canada Ltd. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube of Canada Ltd.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube of Canada Ltd. shall not be liable for incidental or consequential damages.