

# MARINE WIRE ROPE & HAWSER GREASE™



## TECHNICAL DATA SHEET

3820 - 97 Street, NW, Edmonton, Alberta Canada T6E 5S8 • Phone (780) 463-7441 Toll Free 1-888-771-7775 Fax (780) 463-7454 Toll Free 1-888-449-4449  
email: sales@jetlubecanada.com Web site: www.jetlubecanada.com

### DESCRIPTION

**MARINE WIRE ROPE & HAWSER GREASE™** is an economical high performance lubricant for wire rope, hawser and related applications requiring a water resistant, tenacious product that resists the effects of fresh and salt water spray, oxidation, humidity, heat and other adverse conditions common to marine and heavy industrial applications.

**MARINE WIRE ROPE & HAWSER GREASE** maintains and extends the life and performance of wire rope by providing a nondrying film on the outside of the wire rope. This film protects wire rope from corrosion while lubricating the inner strands, drums and sheaves.

- White/Beige Color
- High Temperature
- Anti-Corrosive
- Protects
- NLGI Grade 2
- Nonstaining
- Water Resistant
- Lubricates
- Nondrying

### APPLICATIONS

Recommended for all marine and industrial wire rope, hawser and related activities such as shipyard gantry cranes, mast hoisting cables, loading cranes, offshore rig anchor cables, crane and drag lines, elevator hoist lines or any wire rope cable that operates in harsh conditions.

### CETIFICATIONS

Meets or exceeds requirements of  
U.S. Military Specification Mil-G-18458B (SH)

#### OPERATING RANGE

-18°C to 163°C 0°F to 325°F

### PRODUCT SPECIFICATIONS

Thickener	Lithium
Fluid Type	Petroleum Oil
Color/Appearance	White/Beige Sticky Grease
Dropping Point (ASTM D-2265)	199°C (390°F)
Density (kg/liter), Typical	0.95
Specific Gravity, Typical	0.95
Flash Point (ASTM D-92)	>221°C (439°F)
Additives	Boundary Lubricants, Polymers, R&O
Cone Penetration (ASTM D-217)	265 - 295
Copper Strip Corrosion (ASTM D-4048)	1B
4-Ball Weld Point	315 Min.
Base Oil Viscosity	ISO 220, Typical
Oil Separation (Fed. Std. 791 M 321.2)	5% Max.
Volatile Matter	Less than 2.0%

### PACKAGING

Inventory Code	Container Size	Container
34516	35 Lb.	Pail



### LIMITED WARRANTY

Jet-Lube of Canada makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube of Canada Ltd. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube of Canada Ltd.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube of Canada Ltd. shall not be liable for incidental or consequential damages.