

# SHEEN FREE™

Wire Rope Preservative/Lubricant



## TECHNICAL DATA SHEET

3820 - 97 Street, NW, Edmonton, Alberta Canada T6E 5S8 • Phone (780) 463-7441 Toll Free 1-888-771-7775 Fax (780) 463-7454 Toll Free 1-888-449-4449  
email: sales@jetlubecanada.com Web site: www.jetlubecanada.com

### DESCRIPTION

**JET-LUBE SHEEN-FREE™** is essential to the lubrication of wire ropes. This product not only protects the outside of the wire, but also penetrates into the inner strands to lubricate and reduce corrosion and friction. This anti-friction characteristic is the key to extending the life of the cable. **SHEEN-FREE's** protective film is a nonhazardous, biodegradable, nonsheening preservative and lubricant ideal for the marine industry. The protective film cures to a soft, flexible, tack-free film that resists the buildup of dust and dirt that cause friction and wear within the wire's core. **SHEEN-FREE's** formula was developed to reduce the potential for spontaneous combustion that is so common with the standard linseed oil based product. **SHEEN-FREE** becomes nearly spontaneous combustion free. That is a real plus for safety and housekeeping. The translucent, amber color of this product reduces the housekeeping or custodial efforts over the old asphaltic, black oil type lubricants.

### APPLICATIONS

**SHEEN-FREE** is ideal for standing rigging where a water resistant coating is necessary, and for running rigging where the performance is a must. It is also recommended for bright/black wire, stainless steel and galvanized cables for mooring and lashing applications.

**SHEEN-FREE** can be applied by swabbing, brushing or spraying the product directly onto the cable surface. It is recommended to allow the product to stand in place to form its protective surface film and completely adhere to the metal.

#### OPERATING RANGE:

-10°C to 205°C (-14°F to 400°F)

### CERTIFICATIONS



### CHARACTERISTICS

- Penetrates to wire rope core to provide "inner-strand" lubricity.
- Displaces water while coating scratches and nicks.
- Forms an outer film to protect against salt water corrosion and washoff.
- Meets and exceeds USCG specifications.
- Biodegradable
- Flexible finish
- No evaporation
- Nonhazardous
- 24 Hour Cure Time

### PACKAGING

Inventory Code	Container Size	Container
33720	5 gal	Pail
33724	15 gal	Drum
33729	50 gal	Drum



### LIMITED WARRANTY

Jet-Lube of Canada makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube of Canada Ltd. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube of Canada Ltd.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube of Canada Ltd. shall not be liable for incidental or consequential damages.